

Fresa de corte recto para pantógrafo




HERRAMIENTA HW
CON CORTE FRONTAL



113



D mm	I mm	L mm	S mm		CÓDIGO Rotación derecha
12	26	52	12	10	113.120.11
12	40	70	12	10	113.121.11
13	26	52	12	10	113.130.11
14	28	56	12	10	113.140.11
14	40	72	12	10	113.141.11
15	32	60	12	10	113.150.11
16	32	60	12	10	113.160.11
16	40	72	12	10	113.161.11
17	35	64	12	10	113.170.11
18	35	64	12	10	113.180.11
19	38	68	12	1	113.190.11
20	38	68	12	1	113.200.11
22	40	72	12	1	113.220.11
24	40	72	12	1	113.240.11
25	40	72	12	1	113.250.11
26	42	74	12	1	113.260.11
28	42	74	12	1	113.280.11
30	42	74	12	1	113.300.11

CARACTERÍSTICAS TÉCNICAS:

- Realizada en acero especial de alta resistencia
- 2 cortes HW [Z2]
- 1 corte HW [Z1] para taladrar

EMPLEO: para taladrar y contornear la madera maciza y sus derivados. También para laminados y material plástico. Para montar en mandriles o adaptadores para centros de trabajo, máquinas punto/punto y pantógrafos de CNC.